

Mercury 30HP EFI Four Stroke

\$7,890



HP / kW	<ul style="list-style-type: none"> • 30 / 22.4
Engine type	<ul style="list-style-type: none"> • Inline 3
Displacement (CID/CC)	<ul style="list-style-type: none"> • 32.1 / 526
Full throttle RPM	<ul style="list-style-type: none"> • 5250-6250
Fuel induction system	<ul style="list-style-type: none"> • 2 valves per cylinder, single overhead cam (SOHC)
Alternator amp / Watt	<ul style="list-style-type: none"> • 15 amp / 186 watt
Recommended fuel	<ul style="list-style-type: none"> • 87% octane / up to 10% ethanol
Recommended oil	<ul style="list-style-type: none"> • Mercury FourStroke Oil 10W-30
Engine protection operator warning system	<ul style="list-style-type: none"> • Low oil pressure • Over-rev • Overheat • Sensor failure
Starting	<ul style="list-style-type: none"> • Electric (turn-key) • Manual
Steering	<ul style="list-style-type: none"> • Remote • Tiller
Shaft length	<ul style="list-style-type: none"> • 15" / 381 mm • 20" / 508 mm
Gearcase ratio	<ul style="list-style-type: none"> • 1.92:1
Dry weight *Lightest model available	<ul style="list-style-type: none"> • 172 lbs / 78 kg
CARB star rating	<ul style="list-style-type: none"> • 3
Bore and stroke	<ul style="list-style-type: none"> • 2.40 x 2.36" / 61 x 60 mm
Ignition	<ul style="list-style-type: none"> • CDI w/electronic spark advance
Fuel system	<ul style="list-style-type: none"> • Electronic Fuel Injection (EFI)
Cooling system	<ul style="list-style-type: none"> • Water-cooled with thermostat
Gear shift	<ul style="list-style-type: none"> • F-N-R
Gearcase options	<ul style="list-style-type: none"> • Standard • Gas assist
Trim system	

- Exhaust system

Shallow water trim range (degrees)

Remote fuel tank standard (gal / L)

Color
- Through prop
 - 16
 - 6.6 / 25
 - Phantom Black