

Mercury 250HP Pro Four Stroke

\$40,783



| | |
|--|--|
| HP / kW | <ul style="list-style-type: none">• 250 / 186 |
| Engine type | <ul style="list-style-type: none">• Inline 6 |
| Displacement (L) | <ul style="list-style-type: none">• 2.6 |
| Displacement (L) | <ul style="list-style-type: none">• 2.6 |
| Full throttle RPM | <ul style="list-style-type: none">• 5800-6400 |
| Air induction | <ul style="list-style-type: none">• Supercharged with charge air cooling and electronic boost pressure control |
| Fuel induction system | <ul style="list-style-type: none">• Sequential multi-port electronic fuel injection (EFI) |
| Alternator amp / Watt | <ul style="list-style-type: none">• 70 amp / 882 watt (Belt-Driven) |
| Recommended fuel | <ul style="list-style-type: none">• Unleaded Regular 87 Octane Minimum (R+M/2) or 90 RON 10% Ethanol Maximum• 92 octane for premium performance in all conditions |
| Recommended oil | <ul style="list-style-type: none">• Mercury FourStroke 25W40 Marine Oil |
| Engine protection operator warning system | <ul style="list-style-type: none">• SmartCraft Engine Guardian |
| Compatible with SmartCraft digital technology | <ul style="list-style-type: none">• Yes |
| Starting | <ul style="list-style-type: none">• Smart Start Electric |
| Controls | <ul style="list-style-type: none">• SmartCraft Digital |
| Steering | <ul style="list-style-type: none">• Electro-hydraulic power steering |
| Shaft length | <ul style="list-style-type: none">• 20" / 508 mm• 25" / 635 mm |
| Gearcase ratio | <ul style="list-style-type: none">• 1.85:1 |
| Dry weight *Lightest model available | <ul style="list-style-type: none">• 635 lbs / 288 kg |
| CARB star rating | <ul style="list-style-type: none">• 2 |
| Gearcase options | <ul style="list-style-type: none">• 4.8" |
| Color | <ul style="list-style-type: none">• Phantom Black |