

Mercury 3.5HP Four Stroke

\$1,975



HP / kW	<ul style="list-style-type: none">• 3.5 / 2.6
Engine type	<ul style="list-style-type: none">• 1 cylinder
Displacement (CID/CC)	<ul style="list-style-type: none">• 5.2 / 85
Full throttle RPM	<ul style="list-style-type: none">• 5000-6000
Fuel induction system	<ul style="list-style-type: none">• 2-valve pushrod (overhead valve)
Recommended fuel	<ul style="list-style-type: none">• 87% octane / up to 10% ethanol
Recommended oil	<ul style="list-style-type: none">• Mercury FourStroke Oil 10W-30
Engine protection operator warning system	<ul style="list-style-type: none">• Over-rev
Starting	<ul style="list-style-type: none">• Manual
Steering	<ul style="list-style-type: none">• Tiller with 360° turning
Shaft length	<ul style="list-style-type: none">• 15" / 381 mm• 20" / 508 mm
Gearcase ratio	<ul style="list-style-type: none">• 2.15:1
Dry weight	<ul style="list-style-type: none">• 38 lbs / 17 kg
CARB star rating	<ul style="list-style-type: none">• 3
Emissions Star Rating	<ul style="list-style-type: none">• 3
Bore and stroke	<ul style="list-style-type: none">• 2.16 x 1.42" / 55 x 36 mm
Ignition	<ul style="list-style-type: none">• CDI w/electronic spark advance
Fuel system	<ul style="list-style-type: none">• Carbureted
Cooling system	<ul style="list-style-type: none">• Water-cooled with thermostat
Gear shift	<ul style="list-style-type: none">• F-N
Gearcase options	<ul style="list-style-type: none">• Standard
Trim system	<ul style="list-style-type: none">• 4 position
Trim positions	<ul style="list-style-type: none">• 4
Exhaust system	<ul style="list-style-type: none">• Above prop
Shallow water trim range (degrees)	<ul style="list-style-type: none">• 10-15

Integrated fuel tank (gal / L)

Color

- 0.3 / 1.1
- Phantom Black