

Mercury 4HP Four Stroke

\$2,326



HP / kW	<ul style="list-style-type: none">• 4 / 2.9
Engine type	<ul style="list-style-type: none">• 1 cylinder
Displacement (CID/CC)	<ul style="list-style-type: none">• 7.5 / 123
Full throttle RPM	<ul style="list-style-type: none">• 4500-5500
Fuel induction system	<ul style="list-style-type: none">• 2-valve pushrod (overhead valve)
Alternator amp / Watt	<ul style="list-style-type: none">• 4 lighting / 2 charging amp / 50 lighting / 25 charging watt (Optional)
Recommended fuel	<ul style="list-style-type: none">• 87% octane / up to 10% ethanol
Recommended oil	<ul style="list-style-type: none">• Mercury FourStroke Oil 10W-30
Engine protection operator warning system	<ul style="list-style-type: none">• Low oil pressure• Over-rev
Starting	<ul style="list-style-type: none">• Manual
Steering	<ul style="list-style-type: none">• Tiller
Shaft length	<ul style="list-style-type: none">• 15" / 381 mm• 20" / 508 mm
Gearcase ratio	<ul style="list-style-type: none">• 2.15:1
Dry weight	<ul style="list-style-type: none">• 57 lbs / 26 kg
CARB star rating	<ul style="list-style-type: none">• 3
Bore and stroke	<ul style="list-style-type: none">• 2.32 x 1.77" / 59 x 45 mm
Ignition	<ul style="list-style-type: none">• CDI w/electronic spark advance
Fuel system	<ul style="list-style-type: none">• Carbureted
Cooling system	<ul style="list-style-type: none">• Water-cooled with thermostat
Gear shift	<ul style="list-style-type: none">• F-N-R
Gearcase options	<ul style="list-style-type: none">• Standard
Trim positions	<ul style="list-style-type: none">• 6
Exhaust system	<ul style="list-style-type: none">• Through prop
Shallow water drive	<ul style="list-style-type: none">• Yes
Shallow water trim range (degrees)	<ul style="list-style-type: none">• 16

Optional fuel tank (gal / L)
Color

- 3.2 / 12
- Phantom Black