

## Mercury 9.9HP Four Stroke

\$4,245



<b>HP / kW</b>	<ul style="list-style-type: none"> <li>• 9.9 / 7.3</li> </ul>
<b>Engine type</b>	<ul style="list-style-type: none"> <li>• Inline 2</li> </ul>
<b>Displacement (CID/CC)</b>	<ul style="list-style-type: none"> <li>• 12.8 / 208</li> </ul>
<b>Full throttle RPM</b>	<ul style="list-style-type: none"> <li>• 5000-6000</li> </ul>
<b>Fuel induction system</b>	<ul style="list-style-type: none"> <li>• 2 valves per cylinder, single overhead cam (SOHC)</li> </ul>
<b>Alternator amp / Watt</b>	<ul style="list-style-type: none"> <li>• 6 amp / 76 watt</li> </ul>
<b>Recommended fuel</b>	<ul style="list-style-type: none"> <li>• 87% octane / up to 10% ethanol</li> </ul>
<b>Recommended oil</b>	<ul style="list-style-type: none"> <li>• Mercury FourStroke Oil 10W-30</li> </ul>
<b>Engine protection operator warning system</b>	<ul style="list-style-type: none"> <li>• Low oil pressure</li> <li>• Over-rev</li> </ul>
<b>Starting</b>	<ul style="list-style-type: none"> <li>• Electric</li> <li>• Manual</li> </ul>
<b>Steering</b>	<ul style="list-style-type: none"> <li>• Remote</li> <li>• Tiller</li> </ul>
<b>Shaft length</b>	<ul style="list-style-type: none"> <li>• 15" / 381 mm</li> <li>• 20" / 508 mm</li> </ul>
<b>Gearcase ratio</b>	<ul style="list-style-type: none"> <li>• 2.08:1</li> </ul>
<b>Dry weight *Lightest model available</b>	<ul style="list-style-type: none"> <li>• 84 lbs / 38 kg</li> </ul>
<b>CARB star rating</b>	<ul style="list-style-type: none"> <li>• 3</li> </ul>
<b>Bore and stroke</b>	<ul style="list-style-type: none"> <li>• 2.16 x 1.73" / 55 x 44 mm</li> </ul>
<b>Ignition</b>	<ul style="list-style-type: none"> <li>• CDI w/electronic spark advance</li> </ul>
<b>Fuel system</b>	<ul style="list-style-type: none"> <li>• Carbureted</li> </ul>
<b>Cooling system</b>	<ul style="list-style-type: none"> <li>• Water-cooled with thermostat</li> </ul>
<b>Gear shift</b>	<ul style="list-style-type: none"> <li>• F-N-R</li> </ul>
<b>Gearcase options</b>	<ul style="list-style-type: none"> <li>• Standard</li> </ul>
<b>Trim positions</b>	<ul style="list-style-type: none"> <li>• Ratcheting</li> </ul>
<b>Exhaust system</b>	<ul style="list-style-type: none"> <li>• Through prop</li> </ul>
<b>Shallow water drive</b>	<ul style="list-style-type: none"> <li>• Yes</li> </ul>
<b>Shallow water trim range (degrees)</b>	<ul style="list-style-type: none"> <li>• 18</li> </ul>

**Remote fuel tank standard (gal / L)**

**Color**

- 3.2 / 12
- Phantom Black