

## Mercury 20HP Four Stroke

\$6,335



|  |   |
|--|---|
| <b>HP / kW</b>                                   | <ul style="list-style-type: none"><li>• 20 / 14.7</li></ul>   |
| <b>Engine type</b>                               | <ul style="list-style-type: none"><li>• Inline 2</li></ul>  |
| <b>Displacement (CID/CC)</b>                     | <ul style="list-style-type: none"><li>• 21.4 / 351</li></ul>  |
| <b>Full throttle RPM</b>                         | <ul style="list-style-type: none"><li>• 5400-6100</li></ul>   |
| <b>Fuel induction system</b>                     | <ul style="list-style-type: none"><li>• 2 valves per cylinder, single overhead cam (SOHC)</li></ul> |
| <b>Alternator amp / Watt</b>                     | <ul style="list-style-type: none"><li>• 12 amp / 138 watt</li></ul>                                 |
| <b>Recommended fuel</b>                          | <ul style="list-style-type: none"><li>• 87% octane / up to 10% ethanol</li></ul>                    |
| <b>Recommended oil</b>                           | <ul style="list-style-type: none"><li>• Mercury FourStroke Oil 10W-30</li></ul>                     |
| <b>Engine protection operator warning system</b> | <ul style="list-style-type: none"><li>• Low oil pressure</li><li>• Over-rev</li></ul>               |
| <b>Starting</b>                                  | <ul style="list-style-type: none"><li>• Electric</li><li>• Manual</li></ul>                         |
| <b>Steering</b>                                  | <ul style="list-style-type: none"><li>• Remote</li><li>• Tiller</li></ul>                           |
| <b>Shaft length</b>                              | <ul style="list-style-type: none"><li>• 15" / 381 mm</li><li>• 20" / 508 mm</li></ul>               |
| <b>Gearcase ratio</b>                            | <ul style="list-style-type: none"><li>• 2.15:1</li></ul>  |
| <b>Dry weight *Lightest model available</b>      | <ul style="list-style-type: none"><li>• 115 lbs / 52 kg</li></ul>                                   |
| <b>CARB star rating</b>                          | <ul style="list-style-type: none"><li>• 3</li></ul>   |
| <b>Bore and stroke</b>                           | <ul style="list-style-type: none"><li>• 2.40 x 2.36" / 61 x 60 mm</li></ul>                         |
| <b>Ignition</b>                                  | <ul style="list-style-type: none"><li>• CDI w/electronic spark advance</li></ul>                    |
| <b>Fuel system</b>                               | <ul style="list-style-type: none"><li>• Carbureted</li></ul>  |
| <b>Cooling system</b>                            | <ul style="list-style-type: none"><li>• Water-cooled with thermostat</li></ul>                      |
| <b>Gear shift</b>                                | <ul style="list-style-type: none"><li>• F-N-R</li></ul>   |
| <b>Gearcase options</b>                          | <ul style="list-style-type: none"><li>• Standard</li></ul>  |
| <b>Trim system</b>                               | <ul style="list-style-type: none"><li>• Power Tilt</li></ul>  |
| <b>Trim positions</b>                            | <ul style="list-style-type: none"><li>• 6</li></ul>   |
| <b>Exhaust system</b>                            | <ul style="list-style-type: none"><li>• Through prop</li></ul>                                      |
| <b>Shallow water drive</b>                       |   |

**Shallow water trim range  
(degrees)**

- 16

**Remote fuel tank standard (gal / L)**

- 6.6 / 25

**Color**

- Phantom Black