

Mercury 25HP EFI Four Stroke

\$6,718



| | |
|--|---|
| HP / kW | <ul style="list-style-type: none">• 25 / 18.6 |
| Engine type | <ul style="list-style-type: none">• Inline 3 |
| Displacement (CID/CC) | <ul style="list-style-type: none">• 32.1 / 526 |
| Full throttle RPM | <ul style="list-style-type: none">• 5000-6000 |
| Fuel induction system | <ul style="list-style-type: none">• 2 valves per cylinder, single overhead cam (SOHC) |
| Alternator amp / Watt | <ul style="list-style-type: none">• 15 amp / 186 watt |
| Recommended fuel | <ul style="list-style-type: none">• 87% octane / up to 10% ethanol |
| Recommended oil | <ul style="list-style-type: none">• Mercury FourStroke Oil 10W-30 |
| Engine protection operator warning system | <ul style="list-style-type: none">• Low oil pressure• Over-rev• Overheat• Sensor failure |
| Starting | <ul style="list-style-type: none">• Electric (turn-key)• Manual |
| Steering | <ul style="list-style-type: none">• Remote• Tiller |
| Shaft length | <ul style="list-style-type: none">• 15" / 381 mm• 20" / 508 mm |
| Gearcase ratio | <ul style="list-style-type: none">• 1.92:1 |
| Dry weight *Lightest model available | <ul style="list-style-type: none">• 157 lbs / 71 kg |
| CARB star rating | <ul style="list-style-type: none">• 3 |
| Bore and stroke | <ul style="list-style-type: none">• 2.40 x 2.36" / 61 x 60 mm |
| Ignition | <ul style="list-style-type: none">• CDI w/electronic spark advance |
| Fuel system | <ul style="list-style-type: none">• Electronic Fuel Injection (EFI) |
| Cooling system | <ul style="list-style-type: none">• Water-cooled with thermostat |
| Gear shift | <ul style="list-style-type: none">• F-N-R |
| Gearcase options | <ul style="list-style-type: none">• Standard• Manual |
| Trim system | |

Exhaust system

Shallow water trim range (degrees)

Remote fuel tank standard (gal / L)

Color

- Through prop
- 18
- 6.6 / 25
- Phantom Black