

Mercury 15HP Four Stroke

\$4,995



HP / kW	<ul style="list-style-type: none"> • 15 / 11.1
Engine type	<ul style="list-style-type: none"> • Inline 2
Displacement (CID/CC)	<ul style="list-style-type: none"> • 21.4 / 351
Full throttle RPM	<ul style="list-style-type: none"> • 5000-6000
Fuel induction system	<ul style="list-style-type: none"> • 2 valves per cylinder, single overhead cam (SOHC)
Alternator amp / Watt	<ul style="list-style-type: none"> • 12 amp / 138 watt
Recommended fuel	<ul style="list-style-type: none"> • 87% octane / up to 10% ethanol
Recommended oil	<ul style="list-style-type: none"> • Mercury FourStroke Oil 10W-30
Engine protection operator warning system	<ul style="list-style-type: none"> • Low oil pressure • Over-rev
Starting	<ul style="list-style-type: none"> • Electric • Manual
Steering	<ul style="list-style-type: none"> • Remote • Tiller
Shaft length	<ul style="list-style-type: none"> • 15" / 381 mm • 20" / 508 mm
Gearcase ratio	<ul style="list-style-type: none"> • 2.15:1
Dry weight *Lightest model available	<ul style="list-style-type: none"> • 115 lbs / 52 kg
CARB star rating	<ul style="list-style-type: none"> • 3
Bore and stroke	<ul style="list-style-type: none"> • 2.40 x 2.36" / 61 x 60 mm
Ignition	<ul style="list-style-type: none"> • CDI w/electronic spark advance
Fuel system	<ul style="list-style-type: none"> • Carbureted
Cooling system	<ul style="list-style-type: none"> • Water-cooled with thermostat
Gear shift	<ul style="list-style-type: none"> • F-N-R
Gearcase options	<ul style="list-style-type: none"> • Standard
Trim system	<ul style="list-style-type: none"> • Power Tilt
Trim positions	<ul style="list-style-type: none"> • 6
Exhaust system	<ul style="list-style-type: none"> • Through prop
Shallow water drive	<ul style="list-style-type: none"> • Yes

- Shallow water trim range (degrees) • 16
- Remote fuel tank standard (gal / L) • 6.6 / 25
- Color • Phantom Black