

Mercury 50HP EFI CT Four Stroke

\$12,810



HP / kW	<ul style="list-style-type: none">• 50 / 37
Engine type	<ul style="list-style-type: none">• Inline 4
Displacement (CID/CC)	<ul style="list-style-type: none">• 60.8 / 995
Full throttle RPM	<ul style="list-style-type: none">• 5500-6000
Fuel induction system	<ul style="list-style-type: none">• 2 valves per cylinder, single overhead cam (SOHC)
Alternator amp / Watt	<ul style="list-style-type: none">• 18 amp / 226 watt
Recommended fuel	<ul style="list-style-type: none">• 87% octane / up to 10% ethanol
Recommended oil	<ul style="list-style-type: none">• Mercury FourStroke 25W40 Marine Oil
Engine protection operator warning system	<ul style="list-style-type: none">• SmartCraft Engine Guardian
Compatible with SmartCraft digital technology	<ul style="list-style-type: none">• Yes
Starting	<ul style="list-style-type: none">• Electric (turn-key)• Big Tiller Compatible
Steering	<ul style="list-style-type: none">• Remote• Tiller Kit
Shaft length	<ul style="list-style-type: none">• 20" / 508 mm
Gearcase ratio	<ul style="list-style-type: none">• 2.33:1
Dry weight *Lightest model available	<ul style="list-style-type: none">• 260 lbs / 118 kg
CARB star rating	<ul style="list-style-type: none">• 3
Bore and stroke	<ul style="list-style-type: none">• 2.56 x 2.95" / 65 x 75 mm
Ignition	<ul style="list-style-type: none">• ECM 07 Digital Inductive
Fuel system	<ul style="list-style-type: none">• Electronic Fuel Injection (EFI)
Cooling system	<ul style="list-style-type: none">• Water-cooled with thermostat
Gear shift	<ul style="list-style-type: none">• F-N-R
Gearcase options	<ul style="list-style-type: none">• Command Thrust
Trim system	<ul style="list-style-type: none">• Power Trim
Exhaust system	<ul style="list-style-type: none">• Through prop

Shallow water trim range (degrees)

Remote fuel tank (optional)

Color

- Yes
- Phantom Black